



SINGLE MODULE - LANDSCAPE POLE TOP MOUNT STP-SCR/45R



The STP-SCR/45R is designed and engineered for a single 60 or 72 cell module that is less than 45” wide. Mounts are manufactured using pre-galvanized steel and heavy-duty corrosion resistant 5000 series aluminum.

- Mounts on a user-supplied 4” schedule 40 steel pipe
- No complex sizing documents or need to send module data sheets when ordering
- Easily installed and adjusted by a single person
- Pre-galvanized finish is standard. No up-charges for environmental challenged areas
- Stainless Steel Hardware
- Tilt angle is easily adjustable in 10° increments from 0° to 60° from horizontal
- IN STOCK for immediate ground shipment
- Total shipping weight is 51 pounds in two boxes
- **Certified for up to 150 mph wind speeds and 50 psf snow load at all tilt angles**

Concrete Footing Size for 4" Schedule 40 Steel Pipe					
Tilt Angle Degrees From Horizontal	Class 5		Class 4		Soil Type
	18"	30"	18"	30"	Footing Diameter
0	3.00	2.50	2.75	2.25	Footing Depth (feet)
10	4.00	3.50	3.50	3.00	
20	4.25	3.50	3.50	3.00	
30	5.50	4.50	4.75	3.75	
40	6.25	5.00	5.25	4.25	
50	6.50	5.50	5.75	4.75	
60	7.00	5.75	6.00	4.75	