




# SIDE OF POLE MOUNTS

- For wind speeds up to 180 MPH - see individual data sheets for specific ratings
- Fits pole outside diameters of 2-inch to 4.5-inch
- Adapts to larger poles, Rohn 25-series towers, or flat surfaces with additional fasteners
- Maximum total module surface area is 18.33 square feet
- Fits modules with center to center mounting hole spacing of 19-inches to 39-inches
- Manufactured using heavy-duty corrosion-resistant 5000 series aluminum
- In stock for immediate shipment via ground carriers
- All Tamarack Side-of-Pole Mounts are RoHS compliant



ITEM #	Maximum Module Area (sq. ft.)	Rail Length (inches)	Module Hole Spacing (inches)	Mounting Pole Size (inches)	Mount Style
UNI-SP/01A	7	27.5	18.9 to 28.7	2 to 4.5 O.D.	
UNI-SP/01XH	7	27.5	29.2 to 39.0	2 to 4.5 O.D.	
UNI-SP/01XX	18.33	30	29.2 to 39.0	2 to 4.5 O.D.	
UNI-SP/02	18.33	45	18.9 to 28.7	2 to 4.5 O.D.	
UNI-SP/02A	18.33	55	18.9 to 28.7	2 to 4.5 O.D.	
UNI-SP/02X	18.33	55	29.2 to 39.0	2 to 4.5 O.D.	
UNI-SP/03	18.33	70	18.9 to 28.7	2 to 4.5 O.D.	
UNI-SP/03W	18.33	70	29.2 to 39.0	2 to 4.5 O.D.	

- Mount Two 60 or 72 cell modules on a 4-inch Schedule 40 pipe
- Manufactured from G-90 Galvanized Steel with Stainless Steel Hardware
- Optional SP-HDLP-ADP can be used for mounting to larger or tapered poles

ITEM #	Maximum Module Area (sq. ft.)	Rail Length (inches)	Module Hole Spacing (inches)	Mounting Pole Size (inches)	
UNI-SPHD/4-90	42	90	30 to 56	4-inch schedule 40 pipe	